



Messing- und Sondermessing-Rundstangen

CW614N CuZn39Pb3

CW710R CuZn 5Ni3Mn2AlPb

CW617N CuZn40PB2

Brass-Round-Bars

EN 12164 / 12163 / EN 12165



Ø mm	kg/mtr.	CW 614N	CW 710R	CW 617N
3	0,06	●		
4	0,10	●		
5	0,16	●		
6	0,24	●		
7	0,32	●		
8	0,42	●		
8,5	0,48	●		
9	0,54	●		
9,5	0,60	●		
10	0,67	●		
11	0,81	●		
12	0,96	●		
13	1,13	●		
13,5	1,14	●		
14	1,31	●		
15	1,50	●		
15,5	1,60	●		
16	1,71	●		●
17	1,93	●	●	●
18	2,16	●		●
19	2,41	●		
20	2,67	●		●
21	2,94	●		
22	3,23	●		
23	3,53	●		
24	3,85	●		●

Ø mm	kg/mtr.	CW 614N	CW 710R	CW 617N
25	4,17	●		●
26	4,51	●		
27	4,87	●		
28	5,23	●		
29	5,86	●		
30	6,01	●		●
31	6,42	●		●
32	6,84	●		●
33	7,30	●		●
34	7,72	●		●
35	8,18	●		●
36	8,65	●		
37	9,20	●		
38	9,64	●		●
40	10,70	●		●
42	11,80	●		
44	12,92	●		
45	13,50	●		●
46	14,13	●		●
48	15,40	●		●
50	16,70	●		●
52	18,05	●		
55	20,20	●		●
56	20,94	●		
58	22,46	●		
60	24,00	●		

Ø mm	kg/mtr.	CW 614N	CW 710R	CW 617N
65	28,20	●		
70	32,70	●		
75	37,60	●		
80	42,70	●		
85	48,20	●		
90	54,20	●	●	
95	60,22	●		
100	66,70	●		
105	73,70	●		
110	81,00	●		
115	88,30	●		
120	96,00	●		
125	104,26	●		
130	113,00	●		
140	131,00	●		
150	150,00	●		
160	171,00	●		
170	198,00	●		
180	216,00	●		
200	267,00	●		
210	294,00	●		
225	338,00	●		
250	417,00	●		

Messing- und Sondermessing-Sechskantstangen

CW614N CuZn39Pb3

CW710R CuZn 5Ni3Mn2AlPb

Brass-Hexagonal-Bars

EN 12164 / 12165



Abmessung dimension SW/mm	kg/mtr.	CW614N	CW710R
5	0,18	●	
5,5	0,22	●	
6	0,27	●	
8	0,47	●	
10	0,74	●	
11	0,89	●	
12	1,06	●	
13	1,24	●	●
14	1,44	●	
15	1,60	●	
16	1,88	●	
17	2,13	●	
19	2,66	●	
22	3,56	●	
23	3,76	●	

Abmessung dimension SW/mm	kg/mtr.	CW614N	CW710R
24	4,24	●	
27	5,37	●	
30	6,63	●	
32	7,54	●	●
36	9,54	●	
41	12,37	●	
46	15,58	●	
50	18,40	●	
55	22,27	●	●
60	26,50	●	●
65	31,10	●	
70	36,07	●	
75	41,41	●	
80	47,11	●	