



Messing-Bleche

CW508L

CuZn37

CW612N

CuZn39Pb2

Brass-Sheets

EN 1652

Dicke thk. mm	kg/Tfl. kg/pl.	Abmessung dimension mm	CW508L			CW612N hart hard	Dicke thk. mm	kg/Tfl. kg/pl.	Abmessung dimension mm	CW508L			CW612N hart hard
			weich soft	hh	hart hard					weich soft	hh	hart hard	
0,05	0,081	300 x 650			●		2,5	25,0	600 x 2000	●	●		
0,1	0,5	300 x 2000		●			2,5	42,5	1000 x 2000		●		
0,2	2,0	600 x 2000		●			3,0	30,0	600 x 2000		●		●
0,3	3,0	600 x 2000		●			3,0	51,0	1000 x 2000		●		
0,4	4,0	600 x 2000		●			3,0	82,0	1250 x 2500		●		
0,5	5,0	600 x 2000	●	●			3,0	115,0	1500 x 3000		●		
0,5	8,5	1000 x 2000		●			4,0	40,0	600 x 2000		●		●
0,6	6,0	600 x 2000		●			4,0	68,0	1000 x 2000		●		
0,7	11,9	1000 x 2000		●			4,0	153,0	1500 x 3000		●		
0,8	8,0	600 x 2000	●	●			5,0	50,0	600 x 2000		●		●
0,8	13,6	1000 x 2000		●			5,0	85,0	1000 x 2000		●		
1,0	10,0	600 x 2000	●	●		●	5,0	192,0	1500 x 3000		●		
1,0	17,0	1000 x 2000	●	●			6,0	60,0	600 x 2000			●	
1,0	27,0	1250 x 2500		●			6,0	102,0	1000 x 2000		●		
1,2	12,0	600 x 2000	●	●			6,0	230,0	1500 x 3000		●		
1,5	15,0	600 x 2000	●	●	●	●	7,0	70,0	600 x 2000			●	
1,5	25,5	1000 x 2000	●	●			8,0	80,0	600 x 2000		●		●
1,5	40,0	1250 x 2500		●			8,0	136,0	1000 x 2000		●		
2,0	20,0	600 x 2000	●	●		●	10,0	100,0	600 x 2000		●		●
2,0	34,0	1000 x 2000	●	●			10,0	170,0	1000 x 2000		●		
2,0	53,0	1250 x 2500		●									

Messing-Platten

CW612N

CuZn39Pb2 walzhart *hard rolled*

Brass-Plates

EN 1652

Dicke thk. mm	kg/Tfl. kg/pl.	Abmessung dimension 1020 x 3020 mm	Dicke thk. mm	kg/Tfl. kg/pl.	Abmessung dimension 1020 x 3020 mm	Dicke thk. mm	kg/Tfl. kg/pl.	Abmessung dimension 1020 x 2020 mm
10,0	286,0	●	35,0	917,0	●	80,0	1401,0	●
12,0	314,0	●	40,0	1048,0	●	90,0	1577,0	●
15,0	393,0	●	45,0	1178,0	●	100,0	1751,0	●
20,0	524,0	●	50,0	1309,0	●	120,0	1065,0	1020 x 1020
25,0	655,0	●	60,0	1571,0	●	130,0	1150,0	1020 x 1020
30,0	786,0	●	70,0	1833,0	●	150,0	1330,0	1020 x 1020

Dickentoleranz der Platten nur im Plusbereich.

Thickness tolerance of plates always positiv.