



## Aluminium-Bleche EN AW-1050A (Al 99,5)

### Alu-Sheets

EN 573-3 / 485-1, 2, 4



Dicke mm	kg/ Tfl.	Abmessung <b>1000 x 2000</b> mm		kg/ Tfl.	Abmessung <b>1250 x 2500</b> mm		kg/ Tfl.	Abmessung <b>1500 x 3000</b> mm	
		O/H111 (W7) weich	H14/H24 (F11/G11) halbhart		H14/H24 (F11/G11) halbhart	H14/H24 (F11/G11) halbhart			
0,5	2,8		●						
0,8	4,5		●						
1,0	5,6	●	●	8,4	●	12,2	●	●	●
1,5	8,4	●	●	13,2	●	18,9	●	●	●
2,0	11,2	●	●	17,6	●	25,2	●	●	●
2,5	14,0		●	22,0	●				
3,0	16,8		●	26,4	●	37,8	●	●	●
4,0	22,4		●	35,4	●	50,4	●	●	●
5,0	28,0		●	44,0	●	63,0	●	●	●

## Aluminium-Platten EN AW-1050A, H112 / H14 / O/H111 (Al 99,5 F8 / F11 / W7)

### Alu-Plates

EN 573-3 / 485-1, 2 (6 mm: EN 485-4, ab 8 mm: 485-3 spannungsarm gereckt bzw. gerichtet) *stress relieved by controlled stretching*



Dicke mm	kg/ Tfl.	Abmessung <b>1000 x 2000</b> mm		kg/ Tfl.	Abmessung <b>1250 x 2500</b> mm		kg/ Tfl.	Abmessung <b>1500 x 3000</b> mm	
		●	●		●	●		●	●
6,0	32,4	●	●	50,6	●	72,9	●	●	●
8,0	43,2	●	●	67,5	●	97,2	●	●	●
10,0	54,0	●	●	84,4	●	121,5	●	●	●
12,0	64,8	●	●	101,3	●	145,8	●	●	●
15,0	81,0	●	●	126,6	●	187,5	●	●	●
20,0	108,0	●	●	168,8	●	243,0	●	●	●
25,0	135,0	●	●			304,0	●	●	●
30,0	162,0	●	●			364,5	●	●	●
40,0	216,0	●	●						
50,0	270,0	●	●						
60,0	324,0	●	●						

Toleranzen für Plattenzuschneide entnehmen Sie dem Werkstoffblatt im Anhang, Seite 75.

*Tolerances for plates cutted to size, see attachment, page 75.*