



Aluminium-Bleche EN AW-5083 O/H111 (Al Mg 4,5 Mn W28)

Alu-Sheets

EN 573-3 / 485-1, 2, 3, 4

Dicke mm	kg/Tfl.	Abmessung 1000 x 2000 mm	kg/Tfl.	Abmessung 1250 x 2500 mm	kg/Tfl.	Abmessung 1500 x 3000 mm
1,0	5,6	●				
1,5	8,4	●			18,9	●
2,0	11,2	●	17,7	●	25,2	●
2,5			21,9	●	31,5	●
3,0	16,8	●	26,3	●	37,8	●
4,0	22,4	●	35,4	●	50,4	●
5,0	28,0	●	44,0	●	63,0	●

Aluminium-Platten EN AW-5083 O/H111 (Al Mg 4,5 Mn W28)

Alu-Plates

EN 573-3 / 485-1, 2, 3, spannungsarm gereckt bzw. gerichtet, ab 200 mm walzhart

stress relieved by controlled stretching, above 200 mm rolled as hard

Dicke mm	kg/Tfl.	Abmessung 1000x2000 mm bzw. 1020x2020 mm	kg/Tfl.	Abmessung 1250x2500 mm bzw. 1270x2520 mm	kg/Tfl.	Abmessung 1500x3000 mm bzw. 1520x3020 mm	Dicke mm	kg/Tfl.	Abmessung 1000x2000 mm bzw. 1020x2020 mm	kg/Tfl.	Abmessung 1500x3000 mm bzw. 1520x3020 mm
6,0	33,6	●	52,8	●	75,6	●	90,0	504,0	●	1134,0	●
8,0	44,8	●	70,4	●	100,8	●	95,0			1197,0	●
10,0	56,0	●	88,0	●	126,0	●	100,0	560,0	●	1260,0	●
12,0	67,2	●	105,6	●	151,2	●	110,0			1386,0	●
15,0	84,0	●	132,0	●	189,0	●	120,0	672,0	●	1512,0	●
20,0	112,0	●	176,0	●	252,0	●	125,0			1575,0	●
25,0	140,0	●	220,0	●	315,0	●	130,0			1638,0	●
30,0	168,0	●	264,0	●	378,0	●	140,0	1232,0	1270 x 2520	1710,0	●
35,0	196,0	●			441,0	●	150,0			1890,0	●
40,0	224,0	●	352,0	●	504,0	●	160,0	906,0	●	1955,0	●
45,0	252,0	●	394,0	●	567,0	●	170,0	935,0	●	2146,0	●
50,0	280,0	●	440,0	●	630,0	●	180,0			2200,0	●
55,0	308,0	●			693,0	●	200,0			2520,0	●
60,0	336,0	●			756,0	●	220,0			2360,0	1520 x 2520*
65,0					819,0	●	230,0			2434,0	1500 x 2520*
70,0	392,0	●	612,5	●	882,0	●	240,0			2891,0	1480 x 2960*
75,0	420,0				945,0	●	250,0			2646,0	1500 x 2520*
80,0	448,0	●	700,0	●	1008,0	●	270,0			2910,0	1400 x 2800*
85,0					1071,0	●					

Alle diese Bleche und Platten sind grundsätzlich gestempelt.

All these sheets and plates are stamped.

Auf Wunsch erhalten Sie ein Abnahmeprüfzeugnis EN 10204 - 3.1.

We will provide an EN 10204 - 3.1 test certificate on request.

In EN AW-5083 bis 50 mm in der Regel mit Abnahme AD 2000 - Merkblatt W 6 / 1.

In EN AW-5083 up to 50 mm with test AD 2000 - Merkblatt W 6 / 1.