



Kupfer-Bleche

(SF Cu W.-Nr. 2.0090) **Cu DHP** W.-Nr. CW 024 A

(E Cu W.-Nr. 2.0060) **Cu ETP** W.-Nr. CW 004 A

(SE Cu W.-Nr. 2.0070) **Cu HCP** W.-Nr. CW 021 A

(OF Cu W.-Nr. 2.0040) **Cu OF** W.-Nr. CW 008 A



Copper-Sheets

EN 1652 (DIN 1751 / 1787 / 17670)

Dicke mm	kg/ Tfl.	Abmessung mm	SF-Cu		E-Cu hh	SE-Cu hh	OF-Cu hh
			weich	hh			
0,3	5,4	1000 x 2000	●	●			
0,4	7,1	1000 x 2000		●			
0,5	9,0	1000 x 2000		●			
0,6	10,8	1000 x 2000		●			
0,7	12,5	1000 x 2000		●			
0,8	14,4	1000 x 2000		●			
0,9	16,1	1000 x 2000		●			
1,0	18,0	1000 x 2000	●	●	●		●
1,0	28,0	1250 x 2500		●			
1,2	21,6	1000 x 2000		●			
1,4	25,0	1000 x 2000		●			
1,5	27,0	1000 x 2000	●	●			●
1,5	42,0	1250 x 2500		●			
1,5	60,0	1500 x 3000		●			
1,9	33,8	1000 x 2000		●			
2,0	36,0	1000 x 2000	●	●	●		●
2,0	56,0	1250 x 2500		●			
2,0	80,0	1500 x 3000		●			
2,4	42,8	1000 x 2000		●			
2,5	44,8	1000 x 2000					●
3,0	53,7	1000 x 2000			●		●
3,0	85,0	1250 x 2500				●	
3,0	120,0	1500 x 3000				●	
4,0	72,0	1000 x 2000			●		●
4,0	112,0	1250 x 2500				●	
4,0	160,0	1500 x 3000				●	
5,0	90,0	1000 x 2000			●		●
5,0	140,0	1250 x 2500				●	
5,0	200,0	1500 x 3000				●	
6,0	108,0	1000 x 2000			●		●
6,0	240,0	1500 x 3000				●	
8,0	144,0	1000 x 2000					●
8,0	321,0	1500 x 3000				●	
10,0	180,0	1000 x 2000			●		●
10,0	400,0	1500 x 3000				●	



Kupfer-Platten

(SE Cu, walzhart (W.-Nr. 2.0070)) Cu HCP (W.-Nr. CW 021 A) oder Cu PHC (W.-Nr. CW 020 A)

Copper-Plates

EN 13599 in Anl. (DIN 1787 / 40500)

Dicke mm	kg/Tfl.	Abmessung 1020 x 3020 mm	Dicke mm	kg/Tfl.	Abmessung 1020 x 3020 mm	Dicke mm	kg/Tfl.	Abmessung 1020 x 2020 mm
12,0	330,0	●	35,0	960,0	●	70,0	1285,0	●
15,0	415,0	●	40,0	1100,0	●	80,0	1470,0	●
17,0	470,0	●	45,0	1235,0	●	100,0	1835,0	●
20,0	550,0	●	50,0	1375,0	●	130,0	1210,0	1020 x 1020
25,0	685,0	●	60,0	1645,0	●	150,0	1390,0	1020 x 1020
30,0	825,0	●						

Dickentoleranz der Platten nur im Plusbereich.

Thickness Tolerance of plates always positive.

Kupfer-Nickel-Bleche

(Cu Ni 10 Fe 1 Mn W.-Nr. 2.0872) Cu Ni 10 Fe 1 Mn W.-Nr. CW 352 H

Copper-Nickel-Sheets

EN 1652 (DIN 17664 / 1751)

Dicke mm	kg/Tfl.	Abmessung 1000 x 2000 mm	Dicke mm	kg/Tfl.	Abmessung 1000 x 2000 mm
1,5	27,0	●	6,0	108,0	●
2,0	36,0	●	8,0	144,0	●
3,0	54,0	●	10,0	180,0	●
4,0	72,0	●	12,0	216,0	●
5,0	90,0	●	15,0	267,0	●