



Messing-Rundrohre

(Cu Zn 39 Pb 3 (Ms 58)) ziehart W.-Nr. 2.0401) **Cu Zn 39 Pb 3**
(Cu Zn 37 (Ms 63)) ziehart W.-Nr. 2.0321) **Cu Zn 37**

W.-Nr. CW 614 N
 W.-Nr. CW 508 L



Brass-Round-Tubes

EN 12168 (DIN 1755 / 17660 / 17661)

Abmessung mm	kg/mtr.	Cu Zn 39 Pb 3 (Ms 58)	Cu Zn 37 (Ms 63)
3,5 x 0,4*	0,033		●
6 x 1	0,13		●
8 x 1	0,19		●
8 x 1,5	0,26		●
10 x 1	0,24		●
12 x 1	0,29		●
16 x 1	0,40		●
18 x 2	0,86	●	
19 x 1*	0,48		●
20 x 1	0,51		●
23 x 3,5	1,84	●	
25 x 1	0,65		●
25 x 3,5	2,01	●	
27 x 5	2,94	●	
30 x 1	0,77		●
30 x 2	1,50	●	
40 x 2	2,03	●	
56 x 7	9,26	●	
60 x 5	7,34	●	
75 x 3,5	6,75	●	
75 x 5	9,34	●	

* in Cu Zn 38 Pb 1 (Ms 60 Pb)

Messing-Winkel

(Cu Zn 39 Pb 3 (Ms 58)) W.-Nr. 2.0401) **Cu Zn 41 Pb 1 Al** W.-Nr. CW 620 N

Brass-Angles

EN 12165 (DIN 17660 / 17674)



Abmessung mm	kg/mtr.	Abmessung mm	kg/mtr.	Abmessung mm	kg/mtr.	Abmessung mm	kg/mtr.
10 x 10 x 2	0,31	25 x 25 x 3	1,20	35 x 35 x 3	1,71	50 x 30 x 3	1,96
15 x 15 x 2	0,48	30 x 20 x 3	1,20	35 x 35 x 4	2,26	50 x 50 x 4	3,27
15 x 15 x 3	0,69	30 x 30 x 2	0,99	40 x 40 x 3	1,96	50 x 50 x 5	4,05
20 x 20 x 2	0,65	30 x 30 x 3	1,45	40 x 20 x 3	1,45	60 x 60 x 5	4,93
20 x 20 x 3	0,94	30 x 30 x 4	1,89	40 x 20 x 4	1,89		
25 x 25 x 2	0,82	30 x 30 x 5	2,34	40 x 40 x 4	2,58		

Messing-Sechskantrohr

(Cu Zn 39 Pb 3 (Ms 58)) R430 W.-Nr. CW 614 N

Brass-Hexagonal-Tube



Abmessung SW/mm	kg/mtr.
17 x Rd. 10	1,47